

# 3-Way Manual Directional Control Hydraulic Cartridge Valve

## **Description:**

The 3-Way, 2-Position Manual Detented Directional Control Cartridge valve is suited for all 3-way hydraulic circuit applications where manual operation is desired.

## **Operation:**


All 2-position options require detent option.

#### Features:


- Several actuator options.
- Detented
- Compact size for minimal space requirements.
- Industry standard C10-3 cavity.

## Ratings:

Nominal Rated Flow: 6 GPM (22.7 lpm) Operating Pressure: 5,000 PSI (345 bar) all ports. Operating Temperature: -31 to 250°f (-35 to 121°c) Leak Rate: Less than 82cc (5 in<sup>3</sup>) per minute Approx. Weight: .5 lbs. (0.23 kg)



# PRESSURE DROP / FLOW



Seal Replacement Kits, External:				
SRK-10-3N	Buna-N			
SRK-10-3V	Flurocarbon (Viton)			
Note: Alternate materials available, contact Doering.				

## **Ordering Information:**

Model	Cavity	Spool Fuction	Control	Seal Material	Material/Coating
DMDA	10 3	0 FS-0	K Hand Knob	N Buna-N	Blank Plated Steel
			R Hand Knob, Red	V Viton	SS Stainless Steel
		2 FS-2	S Hand Knob, SST	E EPDM	SS316 316 SST
		4 FS-4	S316 Hand Knob, 316 SST	W Low Temp Buna-N	
		5 FS-5			
		6 FS-6			
		7 FS-7			

